ClearView LED | CV LED MINI



The Best MultiPurpose LED Display

640mm x 480mm One Standard Cabinet Design | Superior Color | Finest Visual Experience



Perfect for cutting-edge technology multipurpose display demands including broadcast, enterprise, hospital, retail, rental, public area and education



Smaller pixel pitch allows for crisper and higher resolution images. ClearView LED module pixel pitches in the range of 1.2 mm to 4.0 mm



Less energy consumption which greatly reduces usage costs



High protection back cover design, lightweight, enhances durability




Superior colors to represent true colors, with high brightness, wider viewing angle and good image sharpness so that each viewing angle is visually optimal



High refresh rate increased to \geq 3840 Hz



Lower screen temperature reduce screen heat and increase stability in daily use



One standard cabinet design applicable to different pixel pitch modules, excellent compatibility. Upgrade screen resolution with low cost

www.image-path.com ©2024 ImagePath Display Company USA. Specification may vary by region, please visit your local store for details. Actual product's feature and specifications are subject to change without notice

ImagePath[™] ClearView LED is perfect for cutting-edge technology multipurpose display demands with a smaller pixel pitch allows for crisper and higher resolution images. Superior colors with high brightness but less energy consumption and lower screen temperature make ClearView LED more stable and durable in daily use. CV LED Mini is designed for applicable to different pixel pitch modules with excellent compatibility

SPECIFICATION CV LED MINI

| Pixel Pitch | P 1.2 mm | P 1.5 mm | P 2.0 mm | P 2.5 mm | P 3.0 mm | P 4.0 mm |
|-----------------------|-----------------------|----------|----------|----------|----------|----------|
| Resolution (pixel) | 512x384 | 416x312 | 320x240 | 256x192 | 208x156 | 160x120 |
| Cabinet Size | 640 mm x 480 mm | | | | | |
| Contrast Ratio | 3500:1 | | | | | |
| Brightness | 600 cd/m² (typ.) | | | | | |
| Color Greyscale (bit) | 12-14bit | | | | | |
| View Angle (Hor/Ver°) | 160/140° | | | | | |
| Refresh Rate | ≥ 3840 Hz | | | | | |
| Energy Saving Power | up to 30% | | | | | |
| Usage (hour/day) | 24/7 | | | | | |
| Panel Material | Die Casting Aluminium | | | | | |
| LED MTBF | up to 100.000* hours | | | | | |



ClearView LED Mini One Standard Cabinet Design 640 mm x 480 mm

Excellent compatibility with pixel pitch modules, allow screen resolution upgrade at low cost

Die Casting Aluminium material, deliver a lighweight cabinet

ImagePath Display Company USA www.image-path.com Powerful | Interactive | Collaborative



www.image-path.com ©2024 ImagePath Display Company USA. Specification may vary by region, please visit your local store for details. Actual product's feature and specifications are subject to change without notice