

Interactive Collaboration Tool M Ultimate | ICT M Ultimate Series

The Ultimate Collaboration Series for Perfect Meetings and Effective Teaching

Presentation | Collaboration | 360° Video Conferencing Camera | No Apps, Share Files Wirelessly







widescreen ImagePath™ ICT M Ultimate, which ensu perfect color, and rich details OS Android 13, pre-loaded with various apps †

conferencing better with the versatile 4K UHD resolution

business and teaching presentation including Web Browser, Media Player, Whiteboard, and allows you to annotate any app, website, document, or image

Al-based 360° video conferencing device, which equipped with 360° lens, 8 Omni directional Mics - 18 feet voice pickup, noise reduction and wide dynamic range Hi-Fi Speaker, and built-in android system

Connect wirelessly without apps installation and share



content from PC, Mac, Tablet or Smartphone. Control your devices wirelessly with Touchback Control feature. Ensure your meeting keeps on topic with Moderator Control feature





Comes with the new Seamless Bonding Technology touch display features, provides a smooth writing experience, ensures excellent bright, and sharp images

points have been grafted into this ICT M Ultimate for an extraordinary interactive touch experience



Dual Operating System option is available with the addition of Windows 11 Pro, and high-speed Core i7 processor technology



8 Omni-Directional Mics •



All-in-One Camera 360

Display Company USA Specification may yary by ragion please visit your local store for details. Actual product's feature and specifications are subject to change without potice



Document Viewer

View and present your files directly from the ImagePath[™] ICT M Ultimate Series front panel :

- Display files Power Point, Word, Excel, and PDF, as well as most photos and video file format
- Easily annotate files with digital pens, highlighters and shapes
- Save and share annotated files just after a meeting

Bring Your Own Device, No Apps Installation for Wireless Presentation

Without apps installation, participants can wirelessly connect and share content to Interactive Collaboration Tool M Ultimate display with four or more auxiliary screen devices, such as PC, Mac, Tablet or Smartphone. Control devices wirelessly and Moderator controls feature, making meetings and teaching easier, more collaborative, and productive

360 °AI Based Camera for Perfection Video Conferencing

Connect instantly with people worldwide to visually collaborate and share ideas with less time and money. ImagePath[™] ICT M Ultimate Series is the best video conferencing terminal, equipped with 4K resolution screen, integrated audio, and AI based 360 ° Full HD video camera, 8 Omni directional mics and HiFI Speaker. Compatible with world's leading video conferencing brands such as Cisco WebEx, Skype for Business, Vidyo, Pexip, Zoom, Polycom, Microsoft Teams, Avaya, Google Meet and more



360 ° Meeting without Blind Spot



All-in-One Camera 360

w.image-path.com ©2025 ImagePath Display Company USA. Specification may vary by region, please visit your local store for details. Actual product's feature and specifications are subject to change without notice

SPECIFICATION INTERACTIVE COLLABORATION TOOL M ULTIMATE								
	Туре	Interactive Collaboration Tool M Ultimate (ICT M Ultimate)						
Display	Size	55" 65" 75" 86"				98″		
	Display Touch Technology	New Seamless Bonding Technology						
	Backlight Type	D-LED						
	Resolution display	3840 x 2160 (pixel,RGB)						
	Brightness	400cd/m ² (typ.) 450cd/m ² (typ.)						
	Contrast Ratio	1200:1 (typical) , 30000:1 (dynamic)						
	Response Time	8ms(typ.)						
	Refresh Rate	60Hz						
	Viewing Angle	178°(H) / 178°(V)						
	Life time	30.000 hours (typ.)*						
	Display Colors	1.078 (8bit+FRC)						
	Color Gamut(X% NTSC)	72%(typ)						
	View Area H x V (mm)	1209.6 x 680.4	1428.5 x 803.5	1649.7 x 927.9	1895 x 1065.9	2158.8 x 1214.3		
		AI-Based 360° Field of View - 1080 FHD Camera						
		Intelligent Tracking & Auto Focus						
		8 Omni-directional mics, 18 feet voice pickup						
	All-in One Camera	Hi-Fi Speaker						
			USB Type C , USB 2.0, HDMI Port					
		WiFi 5G, Bluetooth BT4.1, RJ45 Network Connection						
Ultimate		Mirorring from Multi-types Devices						
System		No Apps Installation Plug (2 dongle transmitter available), Click & Cast Cross Platform Compatibility, split screen 4 devices Touchback Control Devices						
	Wireless Presentation							
		Moderator (Host) Controls						
		Point-to-point 5 GHz Wi-Fi network connectivity						
		up to 30 meters wireless connectivity						
	Operating System	Yes, Android 13						
	CPU Core	Quad Core						
	Chipset	Mediatek A311D2						
Processing	CPU Architecture	ARM A73+A53						
FIOCESSING	CPU Working Frequency	2.2GHz						
	GPU	MaliG52MP8						
	RAM	4GB DDR up to 8GB						
	ROM	32GB up to 64GB						
Electrical	Power Requirement	AC 100 V – 240 V, 50/60 Hz						
	Standby Condition	<0.5W						
	Audio Output Power	2 x 10W/8Ω 2 x 15W/8Ω 2 x 16W/8Ω				2 x 16W/8Ω		
	Power Consumption	210W	220W	380W	460W	480W		

* the longest operating hours 18/7

	Operating Frequency	2.4GHz/5GHz				
WIFI	Wi-Fi Standard	802.11a/b/g/n/ac				
	Bluetooth	2.1+EDR/4.2/5.1				
	Main Chipset	Mediatek MT7663BU				
	HDMI IN Rear	x2 (HDMI 2.0 up 3840 x 2160 @60Hz),				
	DP IN Rear	(HDMI1 support ARC function) x1 (DP 1.2a up to 3840 x 2160 @60Hz)				
	MIC IN Rear	x1 (3.5mm mini interface)				
	RS232 IN Rear	x1 (interface DB9)				
	Type A USB Rear	x1 USB2.0, x2 USB3.0				
	VGA IN Rear	x1 (DB15 up to 1920 x 1080 @60Hz)				
I/O	Type C USB Rear	x1 (DFP mode only, up to 3840 x 2160 @60Hz)				
	HDMI OUT Rear	x1 (HDMI 2.0 up to up to 3840 x 2160 @60Hz) all channel can be same screen-outed by HDMI				
	SPDIF OUT Rear	x1 (optical)				
	Audio OUT Rear	x1 (3.5mm mini interface)				
	Touch USB Rear	x3 (USB3.0 type-B)				
	LAN Rear	x2 (10M/100/1000M Base-T, RJ45)				
	OPS Rear	x1 (interface: JAE)				
	Type C USB Front	x1 up to 3840 x 2160 @60Hz				
	Public USB Front	x2 (USB3.0, type A)				
	HDMI IN Front	x1 (HDMI 2.0, up to 3840 x 2160 @60Hz -				
	Touch USB Front	x1 (USB2.0, type B) -				
	Sensing Type	Infrared Touch Frame				
	Surface Protection	3.2mm 4.0mm				
	Infrared Touch	Toughened Glass				
	Interpolation Resolution	40 touch points, passive stylus pen 32768 x 32768				
	Touch Accuracy	90% (±1mm)				
	Response Time	90% (± mm) ≤8ms				
Touch	Output Mode	HID Standard				
	Theory Clicks	Unlimited				
	Minimum Touch Object	Single touch ≥1.6mm, Multiple touch ≥2mm				
	Power Consumption	≤2W				
	Multiple Touch	Windows 11/10/8/7, Android				
	Single Touch	Windows XP,Linux, Mac OS,Chrome				
Structure	Housing Material & Color	Aluminum / Metal Plate & Color Black				
	Vesa (mm)	400 x 400 600 x 400 800 x 400 800 x 600 800 x 600				

SPECIFICATION OPS M ULTIMATE SERIES (optional)						
Processor	CPU	Intel [®] Core i5/i7 Latest Generation				
Graphics	Chipset	Intel UHD Graphics				
	Multi Displays	Support Dual displays				
	HDMI OUT	x1 HDMI 1.4 4K resolution @60Hz				
	DP OUT	x1 DP 1.2 4K resolution @60Hz				
Memory	Туре	DDR4				
	Size	8 GB				
Storage	Туре	SSD				
	Size	256 GB				
Ethernet	Interface	10/100/1000Mbps(Gigabit)				
	Connector	x1 RJ45				
Wireless	Interface	x1 M.2 2230 for Wifi+Bluetooth module				
	Front Interface	x1 USB3.0 Type C-USB				
		x2 USB3.0, x2 USB2.0				
I/O		x1 RJ45				
1/0		x1 Line In, x1 Line Out				
		x2 Wi-Fi/Bluetooth ANT				
		x1 Power Button, x1 Reset Button				
OS Supports		Windows 11 Pro				
Power Consumption		60W				

ImagePath Display Company USA www.image-path.com Powerful | Interactive | Collaborative

